







Take advantage of standardization

TM110S is a standard offering package for commercial segment, such as shopping malls, department stores, retail centers, supermarkets, hotels and offices.

KONE TravelMaster 110S escalator (S = Standard)

Dedicated to People Flow™

Try our smart escalator planner tool





Escalator features	TravelMaster 110S main specification
Basic specifications	
Vertical Rise	2.0-8.1 m
Inclination	30 degrees 35 degrees
Installation environment	Indoor
Operating mode	Continuous operation (smart star-delta) Automatic start/stop Stand-by speed Automatic start/stop with stand-by speed
Inverter	No inverter / Smart inverter / Full inverter
Step band speed	0.5 m/s
Drive and gear type	Worm gear with drive chain
Handrail and balustrade	
Handrail type	Black color, C-type
Balustrade type	Glass balustrade, 10 mm safety glass
Balustrade height	900 mm 1000 mm
Step	
Step width	1000 mm
Step material	Stainless steel Aluminum
Step demarcation	Without color demarcation Yellow painting at three sides
Visuals/materials	
Side and soffit cladding material	Hairline stainless steel 304 Hairline stainless steel 430
Decking material	Hairline stainless steel 304
Skirt material	Sheet steel with black anti-friction coating
Front plate material	Black plastic
Comb segment material	Aluminum without painting
Access cover material	Ribbed aluminum



Standardized, limited offering
Competitive pricing
Short lead times
KONE design and quality control like for any other KONE product

Compliance to relevant escalator codes and standards, for example the latest EN115-1:2017

TM110S is guaranteed KONE quality with improved standardization, cost and lead time

Dedicated to People Flow™